



# 65-1 / 65-1H

## 65T Air Hydraulic Jacks

### DESCRIPTION

#### 65-1 Air hydraulic jack

Air hydraulic jack for heavy contractors' machinery

Designed for heavy-duty, intensive commercial use, this jack has a minimum height of 245 mm with an extremely high capacity of 65t

- Hard chromium plated piston rod for long life
- Built-in safety overload valve
- Hand-operated dead-man's control for optimum safety whilst lifting and lowering
- Supplied with 2 extensions (100/200 mm) and pneumatic tyres

*Also available: 65-1TH model with telescopic handle increasing the reach under the vehicle to 2180 mm ensuring safe and easy operation.*

#### 65-1H Air Hydraulic Jack

Air hydraulic jack for heavy duty applications with high clearance. Designed for heavy-duty, intensive commercial use.

- Minimum height of 425 mm
- Maximum height of 725 mm and with extensions up to 1,025 mm
- Hard chromium plated piston rod for long life
- Built-in safety overload valve
- Hand-operated dead-man's control for optimum safety whilst lifting and lowering
- With 2 extensions (100/200 mm)

*Also available: 65-1HTH model with telescopic handle increasing the reach under the vehicle to 2340 mm ensuring safe and easy operation.*



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Denmark 



# 65-1 / 65-1H

## 65T Air Hydraulic Jacks

### DESCRIPTION



Tech Specs	65-1	65-1H
Capacity	65 t	65 t
Min. Height	245 mm	425 mm
Max. Height	380 mm	725 mm
Frame Length	825 mm	980 mm
Handle Length	1,355 mm	1,355 mm
Width with wheels	380 mm	380 mm
Width	200 mm	300 mm
Air supply	9 – 12 bar	9 – 12 bar
Air Consumption	350 l/min	350 l/min
Weight	95 kg	138 kg

— ★★★★★ —  
**PRODUCT OF DENMARK**



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Denmark 