



B25-2

25T/10T Air Hydraulic Jack

DESCRIPTION

Portable air hydraulic jack – ideal for service vans etc

Low minimum height of only 160 mm and low weight of only 28 kg. Handy design – no loose tubes, handles or valves. Easy to operate – handle can be used for carrying, lifting, lowering and manoeuvring.

- Hard chromium plated piston rod for long life
- Built-in safety overload valve
- Hand-operated dead-man's control for optimum safety whilst lifting and lowering
- Transport locking device / wall bracket for both van and workshop (Option)
- With 2 extensions (50/100 mm)

Transport locking device and wall bracket for B25-2

Safe storage in service vans. Pre-vents damages in cases of emergency stops. Neat and practical wall mounting in the workshop.

Optional accessories:

- Extension
- Jack saddle
- V-saddle



Tech Specs	B25-2
Capacity	25t / 10 t
Min. Height	160 mm
Max. Height	235 / 320 mm
Frame Length	535 mm
Handle Length	550 mm
Width with wheels	290 mm
Width	225 mm
Air supply	9 – 12 bar
Air Consumption	350 l/min
Weight	28 kg

PRODUCT OF DENMARK 



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Denmark 