



# FL-2

## Air Hydraulic Twin Ram Jacking Beam

### DESCRIPTION

This model has 2 individually controlled rams offering safe and balanced lifting every time. A rapid and precise air hydraulic unit with high speed ram travel, this dual ram heavy duty model offers a 6t lifting capacity and is ideal for lifting larger vans and trucks.

- Lift capacities 6 / 12 / 16 / 20 tonne
- Dual ram jacking beam
- Transversely sliding rams

Featuring 2 individually controlled rams for safe and balanced lifting, this heavy duty jacking beam has a simple modern design, with the control panels positioned at an ergonomical working height.

This rapid and precise air hydraulic unit with high speed ram travel can be made to fit all lifts due to its adjustable frame (590-890mm or 850-1150mm), with the frame height adjusted and set to your individual specification.

Featuring a dead man's release and safety overload valve you can be assured of speed and safety when in use. Supplied with two 100mm extension.



— ★★★★★ —  
**PRODUCT OF DENMARK**



Tech Specs	FL60-2	FL120-2	FL160-2	FL200-2
Capacity	6,000 kg	12,000 kg	16,000 kg	20,000 kg
Stroke	200 mm	200 mm	200 mm	200 mm
Min Height	305 mm	380 mm	380 mm	380 mm
Max. Height	505 mm	580 mm	580 mm	580 mm
Width <sup>1</sup>	590 – 1,410 mm	590 – 1,410 mm	590 – 1,410 mm	590 – 1,410 mm
Depth	665 mm	665 mm	665 mm	665 mm
Air supply	8 – 12 bar	8 – 12 bar	8 – 12 bar	8 – 12 bar
Air consumption	350 l/min	350 l/min	350 l/min	350 l/min
Weight	202 kg	202 kg	202 kg	202 kg



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Denmark



p.1300 577 541

e. sales@levanta.com.au

www.levanta.com.au