

# LWS028 A110-AB1

## Air-operated double diaphragm pump

### DESCRIPTION

#### Air-operated double diaphragm pump

All our air-operated double diaphragm pumps have simple valves, making them extremely reliable for many applications. All parts can be substituted without opening those parts of the body that are in contact with the fluid.

- Casting: Aluminium
- Compression Ratio: 1:1
- Max. Flow Rate: 110 l/min
- Fluid Connections: 3/4" BSP
- Diaphragm: NBR
- Balls: INOX AISI 316
- Gasket: NBR
- Fluids: Oil – Exhausted Oil – Diesel Fuel



Tech Specs	LWS028 A110-AB1
Fluid Connections	3/4" BSP
Air Connection	3/8" BSP
Max. Flow-rate	110 l/min
Max. Air Pressure	8 bar
Max. Delivery Height	80 m
Max. Suction Lift Dry	6.0 m
Max. Suction Lift Wet	9.8 m
Max. Solid Passing	3.5 mm
Noise Level	72 dB
Displacement per Cycle	100 cm <sup>3</sup>
Mac Viscosity	25,000 cps
Max. Temp	95°C
Weight	7 kg
Measurements (WxLxH)	175 x 265 x 245 mm

→ ★★★★★ ←  
**PRODUCT OF ITALY**

