

DESCRIPTION

Affordable lifting with 7.5T capacity

Mobile column lifts offer you a convenient and flexible lifting option for heavy vehicles.

Their exceptional mobility means column lifts don't take up a fixed space in your workshop and can be easily stored away when not in use. Column lifts allow you to do more with your existing workshop space than alternative lifting option such as fixed four post hoists.

TL75W's wireless configuration means there's no power cables for your technicians to trip over while in your workshop. Heavy duty battery power means there's also no need for 3 phase power supply for your column lifts.

TL75W column lift features

Affordable and cost-effective heavy vehicle lifting

The TechLift brand was conceived in response to a market need for quality lifting equipment at an economical investment value.

High quality rechargeable batteries

The 24V DC power system uses premium quality gel cell storage batteries, which can quickly and easily be recharged using the built-in 240V 10-amp chargers. Battery life between charges will depend on operational factors, but under normal operating conditions you can expect over 20 lifts before recharging is needed.

LCD screen display

- Displays lifting height in real time
- Offers simple troubleshooting of any problems
- Continuously monitors battery condition
- Shows mode type

Cutting-edge safety features

Automatic stop is activated both when the highest point is reached, and in the event of a 50mm height difference between columns.

Advanced synchronisation system

Provides smooth raising and lowering, even when the load is unevenly distributed between columns.



Easy access buttons

Each column features operation & emergency buttons for ease of access.

IP 54 waterproof

Offering protection against dust and moisture.

Tech Specs	TL75W
Capacity	7.5 t per column
Max. lifting height	1,700 mm
Time for Lifting or Lowering	150 seconds
Voltage	24v DC
Motor power	2.2 kW per column
Column dimension	1,300(L)*1,100(W)*2,300(H) mm
Fork length	380 mm
Fork width	280~580 mm
Weight	680 kg
Max. hydraulic pressure	20 Mpa
Battery capacity	20 up & downs (Full charge)
Power supply for charger	240V



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required.