

# Maxi 160, 200 & 240

Electro-mechanical 4-post lift, 16, 20 & 24 t capacity



## Application

- Repair and maintenance

## Description:

- Obstruction system
- Each post equipped with a motor and elastic coupling
- Self-carrying spindles with carrying and safety nuts
- Pushbutton control unit with alarm signal
- One movable platform as standard

### Standard colours:

- Platforms & posts: RAL 7016 - grey
- Ramps: RAL 3020 - red

## Versions:

- Available with different voltages
- Maxi 160 & 200:
  - 3,950 mm flush platforms
  - 7,500 mm flush platforms
  - 8,000 mm flush platforms
  - 8,500 mm flush platforms
  - 9,000 mm flush platforms
- Maxi 240:
  - 2 x 5,000 mm flush platforms
- 1,260, 2,000 or 2,800 mm drive-on ramps
- Drive-on ramps and stops for surface-mounting; alternatively drive-over ramps for recessed installation

## Optional extras:

- Auxiliary jack
- Lighting set
- Scissor jack
- 3rd platform

**Special colours available on request!**



Scan the QR-Code for detailed product information.

Further Information on [www.autopstenhoj.com](http://www.autopstenhoj.com)

**autop Maschinenbau GmbH**

Sandkampstraße 90  
48432 Rheine | Germany

☎ +49 5971 8602-02

☎ +49 5971 8602-25

✉ info@autopstenhoj.com

**STENHØJ A/S**

Barrit Langgade 188-190  
DK-7150 Barrit

☎ +45 76 82 13 30

☎ +45 76 82 13 31

✉ info@autopstenhoj.com

Technical data	
Lifting capacity	16,000 / 20,000 / 24,000 kg
Lifting height	1,850 mm
Stroke length	1,545 / 1,555 mm
Lifting / lowering time	120 sec.
Pump unit	4 x 2.2 / 6 x 2.2 kW
Operation	mechanical
Voltage	3x230 / 400V-50 Hz – 35 / 45 A / 3x230 / 400V-50 Hz – 45 / 60 A

Platforms	
Min. height	295 / 305 mm
Drive-through width	3,200 / 3,470 mm
Width between posts	3,200 / 3,470 mm
Total width	3,920 / 4,190
Total height	2,550 mm
Total length	9,005 / 9,745 / 11,505 / 12,395 mm
Platform length	5,000 / 7,500 / 8,000 / 8,500 / 9,000 mm
Utilization area of platform	variable
Platform width	700 mm
Distance between platforms	950 / 1,180 mm
Wheel base	variable

