



# 25-1 / 25-1H / 25-2

## 25T Air Hydraulic Jacks

### DESCRIPTION

#### 25-1 Air Hydraulic Jack

Single stage air hydraulic jack for heavy plant machinery and trucks

- Minimum height of 220 mm
- Designed for heavy-duty, intensive commercial use
- Hard chromium plated piston rod for long life
- Built-in safety overload valve
- Hand-operated dead-man's control for optimum safety whilst lifting and lowering
- 25-1TH model with telescopic handle increasing the reach under the vehicle to 2,125 mm ensuring safe and easy operation
- With 2 extensions (50/100 mm)

#### 25-1H Air hydraulic jack

Single stage air hydraulic jack for agricultural and contractors' machinery, trailers and other high clearance applications

- Minimum height of 360 mm
- Maximum height of 610 mm, the F250 (optional) extension offers a total extended height of 860 mm
- Hard chromium plated piston rod for long life.
- Built-in safety overload valve
- Hand-operated dead-man's control for optimum safety whilst lifting and lowering
- 25-1HTH model with telescopic handle increasing the reach under the vehicle to 2,170 mm ensuring safe and easy operation
- With 2 extensions (50/100 mm)



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Denmark 



# 25-1 / 25-1H / 25-2

## 25T Air Hydraulic Jacks

### DESCRIPTION

#### 25-2 Air hydraulic jack

Versatile 2-stage jack for buses and trucks

- Minimum height of 180 mm
- Designed for heavy-duty, intensive commercial use
- Hard chromium plated piston rod for long life
- Built-in safety overload valve
- Hand-operated dead-man's control for optimum safety whilst lifting and lowering
- Also available in 25-2TH model with telescopic handle, increasing the reach under the vehicle to 2,125 mm ensuring safe and easy operation
- With 2 extensions (50/100 mm)



Tech Specs	25-1	25-1H	25-2
Capacity	25 t	25 t	25 t
Min. Height	220 mm	360 mm	180 mm
Max. Height	345 mm	610 mm	380 mm
Frame Length	770 mm	820 mm	770 mm
Handle Length	1,355 mm	1,355 mm	1,355 mm
Width with wheels	160 mm	230 mm	160 mm
Width	305 mm	310 mm	305 mm
Air supply	9 – 12 bar	9 – 12 bar	9 – 12 bar
Air Consumption	350 l/min	350 l/min	350 l/min
Weight	62 kg	71 kg	60 kg

— ★★★★★ —  
**PRODUCT OF DENMARK**   
— ★★★★★ —



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Denmark 