



# 40-4

## 40T Air Hydraulic Jack

### DESCRIPTION

#### Key features

##### Extremely low and stable

Low and compact with a high-quality air hydraulic unit secures extremely stable heavy duty lifting

##### Easy to operate

Multi position locking handle with ergonomic pushbuttons makes it very easy to position and operate

##### Long Life Cycle

Rams with special surface treatment and high quality strength steel frame guarantees a long lifecycle

##### Optimum Safety

Built-in overload valve and dead man's release for optimum safety whilst lifting and lowering

##### 2 Standard Extensions

Essential for flexibility. Increases the lifting height by 50 mm or 100 mm

##### Easy to load & Transport

Small handle on the frame makes it easy to lift and handle the jack for transport if needed

##### Optimize with

##### FW SADDLE

Suitable for lifting under bolts, differential gear etc.



##### FW1 V-SADDLE

Suitable for lifting under various axle profiles



#### Tech Specs

40-4

Capacity	40 / 27 / 16 / 10 t
Min. Height	100 mm
Max. Height	145 / 180 / 230 / 275 mm
Frame Length	630 mm
Handle Length	1,160 mm
Width with wheels	235 mm
Width	255 mm
Air supply	6 – 10 bar
Air Consumption	215 l/min
Weight	54 kg



PRODUCT OF DENMARK 



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Denmark 