



# DK20 / DK20Q

## 2T Hydraulic Jack

### DESCRIPTION

#### Hydraulic jacks for low clearance cars

With an extremely low minimum height of 80mm this high lifting, long reach hydraulic jack is ideal for cars with low clearance. Made with a wide and robust frame of high strength steel, this unit is safe, noiseless and ergonomically designed for ease of use.

- 2t lift capacity
- Precise and safe control
- Minimum height of 80mm

Lifting 2t from a low minimum height of 80mm, through to a maximum height of 495mm, this standard lift hydraulic jack is an excellent unit designed for ground hugging cars and vans.

With a wide and robust frame made from high strength steel, the DK20 is loaded with safety features including built-in safety overload and manual dead man's release, providing optimum safety when in use.


The noiseless wheels incorporate polyurethane central O-rings, offering maximum surface protection for the vehicle, while the ergonomically designed handles ensures a positive and safe experience for operators.



Tech Specs	DK20 / DK20Q
Capacity	2,000 kg
Min. Height	80 mm
Max. Height	495 mm
Frame Length	660 mm
Handle Length	950 mm
Frame Height	160 mm
Width	410 mm
Weight	31 kg

PRODUCT OF DENMARK 



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Denmark 



p.1300 577 541

e. sales@levanta.com.au

www.levanta.com.au