



DK40Q/DK60Q

4T-6T Hydraulic Jack

DESCRIPTION

Heavy Duty Hydraulic Jack

Featuring a 4t lifting capacity and an extremely low minimum height of 80mm this low clearance hydraulic jack is ideal for light commercial applications.

Made with a wide and robust frame of high strength steel, this unit is safe, noiseless and ergonomically designed for ease of use.

- 4t lift capacity
- Quick lift pedal
- Minimum height of 80mm

Built with a wide and robust frame made from high strength steel, the DK40Q is fitted with a quick lift pedal for easy reach of lifting point and provides precise and safe control whilst lowering.

Loaded with safety features including built-in safety overload and manual dead man's release, this unit provides optimum safety when lowering. The noiseless wheels incorporating a polyurethane central O-ring offers maximum surface protection for the vehicles, while the ergonomically designed handles ensure a positive and safe experience for operators.



Tech Specs	DK40Q	DK60Q
Capacity	4,000 kg	6,000 kg
Min. Height	140 mm	140 mm
Max. Height	600 mm	600 mm
Frame Length	800 mm	800 mm
Handle Length	950 mm	1,200 mm
Frame Height	240 mm	240 mm
Width	500 mm	500 mm
Weight	95 kg	95 kg

PRODUCT OF DENMARK



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Denmark



p.1300 577 541

e. sales@levanta.com.au

www.levanta.com.au