



F560

56" Wheel Tyre Changer

DESCRIPTION

Clever design allows wheels to be positioned in an instant

Simultaneous movement of the tool-holder carriage and chuck-holder arm allows the wheel to be positioned in an instant. The bead-breaking, fitting and removal tools are incorporated into a single, completely automatic revolving arm.

The controls are located on a movable stand, allowing the operator to work the machine from their chosen position. The moving parts can be operated at two speeds by pressing the relevant pedals on the movable post.

The F560 tyre changer can be supplied with an optional practical radio control (trolley), with multi-channel technology and 2.4 GHz frequency, comprising a transmitter "A" (located on the post) and a receiver (located on the machine). This eliminates any need for a connecting cable, allowing all manoeuvres to be performed without hindrance and from the most convenient position for the operator.

Your workshop can use up to 8 F560 tyre changers connected simultaneously via radio, setting the appropriate available channels.

Functional features:

The universal self-centering chuck is activated by a hydraulic cylinder and can lock all rims from 14 to 58 inches (With PA4V extensions) from the inside or from the central hole. It can rotate in both directions at two different speeds. Four sheets of metal prevent squashing between the chuck flanges.

For total operator safety, a non-return check valve, fitted directly onto the cylinder, keeps the wheel locked even in case of electrical failure or hose rupture.

Tech Specs	F560
Handles rims from	14" - 56"
Max. wheel diameter	2,300 mm
Max. wheel width	1,065 mm
Max. wheel weight	1,000 kg
Working pressure	130 BAR
Gear box motor	1.3/1.85 kW
Pump motor	1.5 kW
Noise level when running	< 70 dB (A)
Machine weight	762 kg
Supply voltage	415V 3PH

— ★★★★★ —
PRODUCT OF ITALY 
— ★★★★★ —

Tyre changer optional extras include:

- Pair of bead clamps
- 2.4 GHz Radio control
- Set of 4 jaws for alloy rims
- Set of 4 extensions from 48" to 58"
- Clamp for alloy rims
- Bead guide lever
- Extra platform
- Roller for tubeless



Specifications/Images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Italy 