



Husky 515

Low PSI double diaphragm pump

DESCRIPTION

Low PSI double diaphragm pump

The Husky 515, ½ inch (12.7mm) double diaphragm pump operates on as little as 20psi (1.4bar, 0.14 MPa). This great double diaphragm pump offers a patented, high-reliability, closed centre air valve that is online serviceable and has an epoxy-coated air section for tough environmental conditions.

- Rugged construction
- Heavy duty design
- Delivery up to 15gpm (56.7pm)

The Husky 515 double diaphragm pump is loaded with features to help you get the job done right, every time, and are built to save you money.

Rugged Construction

Resists corrosion for reliable performance and long life

Heavy-Duty Design

Offers long life, increased productivity and lower overall cost of ownership.

Flow Rates

15gpm (56.7pm)

Lube-Free

Provides for cleaner operation

DataTrak™

Available for each unit to prevent pump runaway and easily track material usage

Fluid Pressure

to 120 psi (8.4Bar, 0.84MPa)

Construction

Polypropylene, PVDF, Aluminium and Stainless Steel

Coating

Epoxy-coated air section for tough environmental conditions

Service

Easy to service air valve for years of dependable performance



Tech Specs	Husky 515
Connection Size	1/2" (12.7 mm)
Thread Type	NPT or BSP
Air Valve	Standard, Smart & Remote
Maximum Flow Rate	16 gpm (61 lpm)
Maximum Discharge Pressure	100 psi (7 bar, 0.7 MPa)
Materials of Construction	Polypropylene, PVDF, Acetal
Centre Section Available	Polypropylene
Pump Weight	6.5 lb (2.9 kg) Polypropylene 7.8 lb (3.5 kg) Acetal 8.5 lb (3.9 kg) PVDF
Maximum Solids	0.094 " (2.5 mm)

PRODUCT OF USA



Specifications/Images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of USA