

DESCRIPTION

5:1 Double-acting air-operated oil pump

- Ratio = 5:1 Delivery capacity 35 l/min
- For wall-fixing or fixed positions
- With different accessories it allows alternative possibilities of application
- Polyurethane seals
- Comes with threaded ring for drum connection

Suitable for oil distribution facilities in workshop for industrial vehicles needing a high delivery with more dispensing points.

These pumps are advised for the transfer of medium-high viscosity oil (SAE 15/240) and anti-freeze, for medium-long distances (150 -200 m).

The delivery capacity of a pump varies according to particular applications and combinations: the pressure of air supplied; viscosity and temperature of the fluid; dimensions of delivery hose; dimensions of connections; and the type of gun which is used.

The operating pressure may vary between a minimum of 3 bar and a maximum of 8 bar. The double-acting guarantee the delivery of a continuous and constant flow, suitable for installations on distribution facilities. To optimise the performance and the time-life of the air-operated pumps, we advise the use of filtered and lubricated air.



Tech Specs	LWS020-1180-000
Compression Ratio	5:1
Working Pressure	6 – 8 bar
Air Consumption Medium	385 l/min
Air Inlet Connection	F 3/8" G BSP
Oil Outlet Connection	M 3/4" G BSP
Oil Delivery Capacity	(6 bar) 35 l/min
Noise	80 dB
Shank Diameter	42 mm
Shank Length	220 mm
Weight	10.1 kg
Volume	0,011
Packing	1

→ ★★★★★ ←
PRODUCT OF ITALY

