

### DESCRIPTION

#### Automatic Tyre Changer

The M824 2V FS LL is a super-automatic tyre changer, suitable for all car, SUV, van and motorcycle wheels.

- 2V version with two-speed motor and tubeless inflating device FS
- Turntable equipped with a patented system to switch the working range from 10 ÷ 20 to 14 ÷ 24 (from outside rim clamping) with a simple manual shift.
- Ergonomic pedals made of aluminum with clear symbol function markings

The Increased Power system makes the rotation speed of the turntable automatically adjustable so the torque remains at the best ratio while at maximum speed. Available only on the M 824 2V FS LL (2-speed version: 6 - 15 rpm).

The turntable can clamp alloy rims from both outside and inside without any damage thanks to its special plastic protection supplied as standard.

The bead breaker arm allows an opening up to 410 mm, and is fitted with a stroke regulator to eliminate the risk of crushing the tyre. The bead breaker is operated by a double-acting pneumatic cylinder made from 100% stainless steel, generating a power of 15500 N on the blade. Plastic guards (supplied as standard), protect alloy rims during the bead-breaking.



Tech Specs	M824 2V FS LL + ALLY90
Supply voltage	240 V
Self centering chuck opening	10" ÷ 24"
Self centering chuck opening	13" ÷ 27"
Bead-breaking power (blade) (10 BAR)	15.000 N
Bead-breaking blade opening	410 mm
Max. wheel diameter	1040 mm
Max. wheel width	14"
Working pressure	10 BAR
Noise level when running	≤70 dB (A)
Two speeds motor (2V)	0,75 KW - 1 PH - 200/230 V-50/60 HZ
Single speed motor	0,75 kW - 3 Ph - 400 V - 50 Hz
Max. self centering torque	1.200Nm
Machine weight (M 824 2V FS LL)	288 kg

\*\*\*\*\*  
**PRODUCT OF ITALY**   
 \*\*\*\*\*



Specifications/Images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of Italy 