



Mini Fire-Ball 225

Durable Performance Based Pump

DESCRIPTION

Durable Performance Based Pump

Perfect for medium pressure, low volume applications, the Mini Fire-Ball 225 is a fantastic pump. You can't afford downtime, especially when your shop is small and your work force depends on equipment performance. An engineered design with fewer moving parts means less to wear out, reduced downtime and more profit for your business.

- Available in 3:1 or 5:1 for oil
- Available in 50:1 for grease
- 7 year warranty

For a solution that works as hard as you do, the hard working Mini Fire-Ball 225 is the best on the market, helping you stay ahead of the competition.

These affordable and full featured pumps are designed for medium pressure, lower volume applications and are available in 3:1 for oil and 50:1 for grease. These pumps are fine-tuned for a compact, flexible and still incredibly durable solution.

The rugged inlet cage withstands demanding shop environments, while the double acting pump offers continuous flow operation, making this unit a versatile, durable and hardworking pump. Typical fluids include lubricating grease, petroleum and synthetic motor oil, hydraulic oil, gear oil, automatic transmission fluid, undercoating and rust-proofing.

These high performance pumps are ideal for use in:

- Fast lubes and small garages
- Oil jobbers
- General service shops
- Dealerships
- Body shops
- Municipalities and transits
- Lube trucks
- Construction equipment
- Fleet maintenance shops
- Manufacturing plants

Key features include:

Durable

Thick cast aluminium air motor housing offers unmatched durability

Fewer Repairs

Fewer moving parts in the air motor assembly means less downtime and low repair cost.

Extended Seal Life

Inline pump design aligns the air motor piston and fluid piston rods to maximise seal life.

Reduce Downtime

Displacement rods have minimal wear due to a proprietary manufacturing process.

Reduced Icing

Large air porting design provides efficient use of compressed air supply for continuous pump operation and reduced icing.

Corrosion Resistant

Corrosion resistance design utilises liquid salt nitriding, nickel plating, stainless steel, aluminium and chrome on key components for longer life.

Three Inch Air Motor

The three inch air motor in every unit provides more power so you get a better flow. With the 3:1 ideal for medium pressure, high flow oil applications and the 5:1 offering a better solution for high pressure, medium flow oil uses, especially for cold temperature or long run applications.

NXT Air Valve

Designed to reduce icing in continuous use applications, these units use less air than competitive pumps offering you better efficiency. They are also easy to repair or replace without tearing down the internal pump components, providing your workshop with less downtime.

Engineered for Durability

The patent-pending cup and plate design eliminates the need for O-rings that regularly wear out, delivering a more durable, longer lasting lubrication solution.

Modular Air Valve

The air inlet and exhaust locations are easy to configure with just four bolts, making installation simple and hassle free in any workshop.

Pilot Valve

Another patent-pending innovation, the self-cleaning design increases reliability in dirty air environments and minimises pressure drop with rapid changeovers, the result reduced stalling and smoother flow.

Adjustable Bung Adapter Included

Making it easier to fit into more applications, each unit includes built-in slide adjustment with easy-set hand screws.

Built-In Thermal Relief and Inlet Strainer

Protect your equipment from thermal expansion without the need to buy and install any additional kit with the built-in thermal relief (oil only) that comes standard with every unit. The oil only inlet strainer is built-in to protect the pump from contaminants that can cause damage.

Specifications/Images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of USA 



Mini Fire-Ball 225

Durable Performance Based Pump

DESCRIPTION

Perfect for medium pressure, low volume applications



Tech Specs	Mini Fire-Ball 225
Dispense Points	1-2
Annual Usage Oil	Up to 113,500 l / 30,000 gal
Annual Usage Grease	Up to 10,000 lb / 4535 kg
Line Length	Up to 250ft / 76 m

PRODUCT OF USA



Specifications/images subject to change without prior notice. Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required. Product of USA